



BETON C30/37 XC1  
OCEL BST500  
KRYTÍ 20 MM

VÝPIS VÝZTUŽE						
OCEL BST500						
POL	PROFIL	DL.	KS	8	12	16
1	16	11,75	127			1492,25
2	16	12,35	35			432,25
3	16	11,35	31			351,85
4	8	4,05	10	40,50		
5	12	4,70	9		42,30	
6	8	5,35	26	139,10		
7	12	6,25	27		168,75	
8	12	1,95	3		5,85	
9	12	11,50	39		448,50	
10	12	9,10	35		318,50	
11	12	8,25	44		363,00	
12	12	7,60	6		45,60	
13	8	8,55	15	128,25		
14	12	5,20	20		104,00	
15	12	5,65	11		62,15	
16	12	2,00	10		20,00	
17	12	0,75	1084		813,00	
CELKOVÁ DELKA (M)				307,85	2291,65	2276,35
HMOTNOST 1m² (KG)				0,394	0,887	1,578
CELKOVÁ HMOTNOST (KG)				121,4	2122,3	3591,0
SPOTŘEBA CELKEM (KG)						5835 KG

HORNÍ VÝZTUŽ DESKY STROPU 1.N.P.  
M 1:100  
Č.v. D1.2.10/2  
DOSTAVBA MŠ ZA FONTÁNOU V PŘELOUČI