



BETON C30/37 XC1
OCEL BST500
KRYTÍ 20 MM

VÝPIS VÝZTUŽE				
OCEL BST500				
POL	PROFIL	DL.	KS	12
1	14	11.70	79	14
2	12	6.55	17	111.35
3	14	10.55	48	506.40
4	14	12.80	33	422.40
5	12	4.10	6	24.60
6	12	6.40	10	64.00
7	12	9.90	26	257.40
8	12	1.80	10	18.00
9	12	6.30	34	214.20
10	12	7.80	6	46.80
11	12	9.10	42	382.20
12	12	7.70	34	261.80
13	12	6.40	39	249.60
14	12	6.55	6	39.30
15	12	6.85	22	150.70
16	12	5.00	17	85.00
17	12	2.00	16	32.00
18	12	0.75	1028	771.00
CELKOVÁ DÉLKA (M)			2707.95	1853.10
HMOTNOST 1m² (KG)			0.887	1.208
CELKOVÁ HMOTNOST (KG)			2402.9	2238.2
SPOTŘEBA CELKEM (KG)				4642 KG

HORNÍ VÝZTUŽ DESKY STROPU 2.N.P.
M 1:100
Č.V. DI.2.11/2
DOSTAVBA MŠ ZA FONTÁNOU V PŘELOUČI